



IDT Os-Series Version 3 Airborne Camera with integrated storage: 8GB of DDR and optional solid-state non-volatile memory of up to 0.5TB. With a maximum resolution of 1600 x 1200 pixels, the OS8 can record up to 1,600 fps. Latest CMOS sensor technology produces extremely low-noise images with up to 12-bit mono or 36-bit color. Support for several sensor platforms to deliver various resolutions and frame rates. Power supply and break-out cable for easy out-of-the-box operation are included.

## KEY FEATURES

Maximum Resolution	1600 x 1200
Maximum FPS @ Maximum Resolution	1,600 fps
Image Storage @ Max Frame Rate (DDR 8)	8,275
Image Storage @ Max Frame Rate (SSD 512)	12,300
Streaming FPS @ Max Resolution	470 fps
Maximum FPS	35,000 @ 1600 x 16
Minimum Exposure Time	1µs
Sensitivity ASA/ISO	6000 ISO Mono 2000 ISO Color
Power Requirements	18-36 VDC
Operating Temperature	-40+50 °C / -40+104 °F

## SENSOR

Sensor Type	CMOS - Proprietary
Sensor Size	13.9 x 10.4 mm
Sensor Format	1.3 inch
Pixel Size (micron)	8.68x8.68 µm
Pixel Depth	12 bit mono 36 bit color

## INPUTS

Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
Sync	Phase-lock TTL
GPS Time Code	Optional

## OUTPUTS

Sync	Frame sync / Strobe
HDSDI	Optional

## FEATURES

Approx. Size	63 x 63 x 87 mm (W x H x L)
Approx. Weight	0.69 kg or 1.52 lbs
Shock/Vibration Rating	Shock: 200G / Vibration: 40G - All axes
Battery Powered Operation Time	Optional
Mount	C-Mount standard , F Adaptor optional

## SOFTWARE

Motion Studio	Windows 32/64
Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF

## COMMUNICATION

Ethernet	1000BaseT
----------	-----------