



## CrashCamMini™

The CrashCam mini HD is a rugged, high-G and vibration-rated camera designed to withstand harsh, space-limited testing environments. With its ultra-compact design, this camera has become the industry standard for on-board vehicular testing and instrumentation of test dummies, but its versatility can be leveraged in any industry. CrashCam mini cameras offer live video streams via HDSDI output, backups through removable MicroSDs and support PTP synchronization. The Model HD supports 1920x1080 resolution with up to 5,850 fps and comes standard with 8GB DDR RAM, USB-C interface and C-mount lens mount. Additional configuration options include a motorized Micro Four Thirds lens mount with airborne feature that includes hydrophobic coating as well as support for GiGE Vision and Chapter 10 IRIG standards.

- Ultra-compact form factor
- HDSDI output
- MicroSD compatible

### APPLICATIONS

Automotive, Research

### KEY FEATURES

Maximum Resolution	1920 x 1080
Maximum FPS @ Maximum Res	5,850 fps
Operating Temperature	-40+50°C / -40+122°F

### FRAME PROPERTIES

Sensor Type	CMOS - Proprietary
Sensor Size	19.2 x 10.8 mm
Sensor Format	1.3 inch
Pixel Size (micron)	7.5 x 7.5 um
Pixel Depth	12 bit mono 36 bit color
Sensitivity	30,000 ISO Mono, 10,000 ISO Color
Min. Exposure Time	1µs (*Shorter Integration optional)
Array	3.7 megapixel
Quantum Efficiency	60%

### MECHANICAL

Weight	0.27 kg or 0.59 lbs
Dimensions	44 x 44 x 70 mm (W x H x L)
Shock & Vibration	Shock: 200G / Vibration: 40G - All axes
Mount	C-Mount (Standard)

### TRIGGERING AND SYNCHRONIZATION

Sync In	Phase-lock TTL, IEEE1588, 1PPS
Sync Out	Frame sync / Strobe
Trigger	TTL & Switch/Circular buffer with on-camera or software trigger
HDSDI	Standard

## Model CCM-HD



### POWER

Input Voltage	7.5-14VDC
---------------	-----------

### COMMUNICATION INTERFACE

Ethernet	2.5 Gbps
----------	----------

### EMBEDDED LOGIC

Debayering	Color Cameras Only
Temporal Noise Reduction	Standard
Dynamic Noise Reduction	Standard
User defined ROI's and LUT's	Standard
Frame to frame Auto-Exposure and Motion Trigger	Standard
Mission Mode for Remote/Autonomous Operation	Standard

### IMAGE CAPACITY

DDR	8GB
MicroSD	Up to 400GB (Tested)

### SOFTWARE

Motion Studio	Windows 32/64
Motion Inspector	Windows 32/64 - MAC OS X - Apple iOS
Plug-ins/SDK	SDK, LabVIEW™ or MatLab®
File Formats	Proprietary RAW
On-the-fly Conversion	TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF